

Monitoare LCD cu margine redusa		VW-46-7B	VW-46-23B
Input	1 x DVI-I	DVI IN	
	1 x HDMI	HDMI IN	
	1 x D-Sub	RGBHV (VGA) IN	
	1 x HD-SDI	HD-SDI IN	
	1xCOMPONENT	YPbPr BNC IN	-
	1x S-VIDEO	Y,C BNC IN	-
	1x CVBS	CVBS BNC IN	-
	1 x 9Pin D-Sub	232 Port	
1 x RJ45 (RS422)	RS422 Port		
Output	1 x DVI-I	DVI Through OUT	-
	1 x HDMI	HDMI Through OUT	-
	1 x D-Sub	RGBHV (VGA) Through OUT	-
	1 x HD-SDI	HD-SDI IN	-
	1xCOMPONENT	YPbPr BNC Through OUT	-
	1x S-VIDEO	Y,C BNC Through OUT	-
	1x CVBS	CVBS BNC Through OUT	-
	1 x RJ45 (RS422)	RS422 Port	
Input Signal	DVI	640x480 / 800x600 / 1024x768 / 1280 x 768 / 1280 x 1024 / 1360 x 768 / 1920 x 1080	
	HDMI	640x480 / 800x600 / 1024x768 / 1280 x 768 / 1280 x 1024 / 1360 x 768 / 1920 x 1080	
	D-Sub	640x480 / 800x600 / 1024x768 / 1280 x 768 / 1280 x 1024 / 1360 x 768 / 1920 x 1080	
	COMPONENT	480i, 480p,720p,1080i,1080p	-
	S-VIDEO	NTSC,PAL	-
	CVBS	NTSC,PAL	-
	HD-SDI	1.485Gbps	
	SD-SDI	270Mbps	
Analog Input Spec	D-Sub	1.0Vpp(With Sync)	
	COMPONENT	1.0Vpp (Y With Sync), 0.286 Vpp (Pb,Pr)	
	S-VIDEO	1.0Vpp (Y With Sync), 0.286 Vpp (C)	
	VIDEO	1.0Vpp(With Sync)	
LCD Control		5 Key ( Menu, Up , Down , Enter/SOURCE , Power )	
		IR Remocon (NEC Protocol)	
		RS422	
Remote	2 x RJ45(RS422)	Standard Direct Cable(UTP Cable) 1 x RJ45(Input) , 1 x RJ45(Output)	
PGM	1 x 9Pin D-Sub	232 Program Update Port	
DVI, VGA, HDMI Input Signal Formats		VESA Standard	
		1920 x 1080 (60P)	
		1920 x 1080 (60i) Only DVI , HDMI	
		1920 x 1080 (50i) Only DVI , HDMI	
SDI Input Signal Formats	SMPTE-274M	1080i (60/59.94/50)	
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)	
	SMPTE-296M	720p(60/59.94/50)	
	SMPTE-260M	1035i(60/59.94)	
	SMPTE-125M	480i(60/59.94)	
ITU-R BT.656	576i (50)		
LCD	Size	46"	46"
	Resolution	1366x768	1920x1080
	Dot Pitch	0.7455 (mm)	0.53025 (mm)
	Color	16.7 M, 8-bit	16.7 M, 8-bit
	Viewing Angle	178 degrees (H)	178 degrees (H)
	(Typical)	178 degrees (V)	178 degrees (V)
	Luminance of White	700cd(center)	700cd(center)
	Contrast	3000:1'	4000:1'
Display Area	1018.353 (H)x572.544 (V)	1018.08 (H)x572.67 (V)	
Power	AC 100 ~ 240 V		
Power Consumption (Approx.)	204 Watts(MAX)		
Operating Temperature	0 °C to 40 °C ( 32 °F to 104 °F)		
Storage Temperature	-10 °C to +50 °C ( 14 °F to 122 °F)		
Main Body Dimensions (mm)/(ft)	1025.6x579.8x106.3(mm)/3.365x1.902x0.348(ft)	1047.4x600x106.3(mm)/3.436x1.970x0.348(ft)	
Weight	27 kg / 59.92 lbs		
	29 kg / 63.93 lbs		